

Product Data Sheet

Version PM1-0218.01

MATRICK 
CEMENT
Specialist Surface Materials


PM1 Pre Sealer

Product Description:

PM1 Pre Sealer is a water based impregnation coating designed to saturate into *MicroCement* products. This protects them from softening, staining and colour change. *PM1 Pre Sealer* is recommended for use before applying any of our solvent or water based polyurethane coatings.

Material Properties:

- ❖ Touch dry within 60 minutes.
- ❖ Overcoat application in 120 minutes (temperature dependant).
- ❖ Once applied, simple flameless combustion @ 250°C (482°F).
- ❖ Minimum application temperature +5°C / Maximum application temperature +25°C.
- ❖ Retention of material properties once cured and applied within the recommended guidelines.
- ❖ High resistance to hydrolysis.



Application Features:

- ❖ Better consumption and saturation achieved at 100% dilution.
- ❖ *PM1 Pre Sealer* can be diluted up to 100%.

Coverage

- 60m²/10Ltrs @ maximum dilution.
- Apply *PM1 Pre Sealer* by Microfiber cloth / brush / foam roller.
- Do not pour directly onto *MicroCement*. Apply from a roller tray.



Packaging:

- ❖ Each carton contains 5L of undiluted liquid.
- ❖ White liquid in appearance.

Matrick Cement LTD reserves the right to change any of the specified instructions on this data sheet without prior notice if necessary.